CONTENTS

Abstract 1
Introduction 1
Purpose and Scope 2
Description of Study Reach 3
Description of the 1993 Flood 3
Simulation of Flow 5
Model Development 6
Calibration of Model to Observed Conditions 6
Simulation of August 6, 1993, Maximum Discharge 8
Simulation of Impendent Discharge 13
Evaluation of Scour 16
Scour Depth Computations in Finite Element Surface-Water Modeling System 16
Scour Depth Computations using Finite Element Surface-Water Modeling System Results 17
Summary 22
References Cited 28

FIGURES

1. Photograph of Horse Island Chute bridge (structure L 1004R1) on Missouri State Highway 51, in Perry County, Missouri, near Chester, Illinois, as viewed from the Bois Brule Levee on the upstream right (southwest) floodplain. The Mississippi River bridge (structure L 135A) and bluff on the Illinois side of the Mississippi River are in the background 2
2. Map showing location of the study reach near Chester, Illinois 4
3. Shaded relief image of study reach near Chester, Illinois, in an oblique perspective facing downstream 5
4. –5. Maps showing:
   4. Finite-element mesh used in flow simulations near Chester, Illinois 7
   5. Land-use coverages used in flow simulations near Chester, Illinois 9
6. Graph showing observed and simulated water-surface elevation profiles for the measured discharge of 944,000 cubic feet per second along the railroad embankment on the Illinois side of the Mississippi River near Chester, Illinois 10
7. –9. Maps showing:
   7. Simulated water-surface elevations for measured discharge of 944,000 cubic feet per second near Chester, Illinois 11
   8. Simulated water-surface elevations for maximum discharge of 1,000,000 cubic feet per second near Chester, Illinois 12
   9. Simulated water-surface elevations for impendent discharge of 894,000 cubic feet per second near Chester, Illinois 14

FIGURES—Continued

10. Graph showing relation between measured discharge in Horse Island Chute (Q_{Chute}) and total measured discharge (Q_{Total}) for the Mississippi River at the U.S. Geological Survey gaging station at Chester, Illinois 15

11.–12. Maps showing:

11. Simulated velocity magnitude using maximum discharge of 1,000,000 cubic feet per second near Chester, Illinois 18

12. Simulated depths and velocity vectors for maximum discharge of 1,000,000 cubic feet per second and flux lines used for scour parameter determimations at Horse Island Chute bridge near Chester, Illinois 19

13.–14. Graphs showing:

13. Contraction and local pier scour depths for simulated maximum discharge of 1,000,000 cubic feet per second through Horse Island Chute bridge near Chester, Illinois 23

14. Total scour depths for three discharge simulations through Horse Island Chute bridge near Chester, Illinois 24

15. Photograph showing stone revetment on abutment face under left (north) end of Horse Island Chute bridge near Chester, Illinois, as viewed from downstream face of bridge 25

16. Graph showing channel bed profiles for: A) small, and B) large flood events at Horse Island Chute bridge near Chester, Illinois 26

17. Photograph showing downstream face of Horse Island Chute bridge near Chester, Illinois, as viewed from downstream face of left (north) embankment. Note debris trapped on upstream face of bents 27

TABLES

1. Manning’s n-values used in model calibration 10
2. Final simulated results for three alternative discharges 13
3. Simulated and calculated discharges through Horse Island Chute bridge 16
4. Contraction scour depths and parameters used to compute scour 20
5. Local pier scour depths and parameters used to compute scour 21
6. Local abutment scour depths and parameters used to compute scour 25

Sea level: In this report, “sea level” refers to the National Geodetic Vertical Datum of 1929 (NGVD of 1929)—a geodetic datum derived from a general adjustment of the first-order level nets of both the United States and Canada, formerly called Sea Level Datum of 1929.